



# Piston Spex Sheet

Powered By EngineWorx

Date: 3/25/2022

Piston Part # WD-14145

[2-Cycle Traveler Click Here](#)

Piston Description:

[4-Cycle Traveler Click here](#)

Piston Specifications	
Bore (IN):	3.7800
Bore (MM):	96.01200
Piston Diameter (IN)	3.7760
Piston Diameter (MM)	95.9104
Dome Volume (CC):	0.0
Material:	2618
Piston Style:	FLAT
Compression Height (IN):	1.3240
Target Weight (G):	485.000
Dome Height (IN):	0.1800
Dome Thickness (IN):	Not Specified
Piston Clearance (IN):	0.0040
Piston Clearance (MM):	0.1016
Pin Offset	0.0300
Pin Offset Direction	HALF EACH WAY
Forging	<a href="#">F6473X</a>

Skirt Mill		
	<i>Intake</i>	<i>Exhaust</i>
Over All Length From TE	2.2900	2.2900

Valve Pocket Specifications		
	<i>Intake</i>	<i>Exhaust</i>
Diameter (IN):	2.1500	1.7500
Angle (DEG):	12.00	12.00
Depth to T/E	-0.1400	-0.1900

2 Cycle		
	Top	Second
Pin Angle	Not Specified	Not Specified
Distance to C/L	Not Specified	Not Specified
Direction	Not Specified	Not Specified

Coating Specifications		
	Coating Type	Coating Thickness
Coating 1	SC	0.0005
Coating 2	Not Specified	Not Specified
Coating 3	Not Specified	Not Specified

Ring Specifications	
Ring Set Part #	Not Specified
Bore (IN):	Not Specified
Bore (MM):	Not Specified
Style:	Not Specified

Wrist Pin Specifications	
Pin Part #:	S749
Diameter (IN):	0.94300
Diameter (MM):	23.95200
Length (IN):	2.25000
Length (MM):	57.15000
Wall Thickness (IN):	0.19590
Wall Thickness (MM):	4.98000
Material:	5115
Coating:	Unchromed
Weight (G):	122.03000

Retainer Clip Specifications	
Retainer Clip Part #	W6045
Diameter (IN):	0.9449
Diameter (MM):	0.0000
Type:	Wire
Thickness (IN):	0.0540
Material:	Chrome Silicon

Stamping Specifications	
Workorder/Date Code?	Y
Entire Part Number?:	Y
Spec Number?:	N
Directional?:	Y
Directional Instructions:	STD LS PIN LASER MARKING



